




TD HANDY-SCAN^{RX} - Multi-Function Ultrasonic Inspection Systems



Features

- Highly Portable
- Sunlight Readable Screen
- Extensive Analysis Tools
- Powerful Reporting Functions
- Removable Battery
- 2 Axis Encoder; Video tracking
- Import setups from ESBeamTool[®]
- Up to x 8 Conventional Channels
- Up to 32/64 Phased Array
- Simultaneous PA, ToFD and/or PE data collection
- 128GB SSD storage

Applications

- Pressure Vessel Welds
- Pipeline Welds
- Corrosion Surveys
- Turbine Disks & Blades
- Complex Geometries
- Forgings & Castings
- Aircraft Components
- Hydrogen Damage Surveys

Techniques

- Phased Array
- ToFD
- Pulse Echo
- Corrosion Mapping
- Weld Zone Discrimination

Software

- Phased Array/Pulse Echo
- ToFD
- Strip-Scan (AUT)
- Long Range (Creep Wave & Corrosion Mapping)
- TD Super-View
- ESBeamTool[®] included

E&OE - All specifications are subject to change. It is advisable to check all information provided.



TD Handy-ScanRX Hardware Specification

Hardware

System Options	
64/32	64 Elements, 32 Active, 8 Conventional
64/16	64 Elements, 16 Active, 4 Conventional
General	
Number Of Focal Laws	1700 max
Dynamic Depth Focusing	Yes
Digitisation	
A/D Sampling Frequency	Phased Array = 8Bit & 14Bit @ 100MHz Conventional = 8Bit & 14Bit @ 100MHz
System Bandwidth(-3dB)	Phased Array = 0.75MHz to 25MHz Conventional = 0.75MHz to 25MHz
Max Pulse Repetition Frequency	Variable up to 5KHz
Pulsar	
Number Of Pulsars	16/32/64
Number Of Active Pulsars	1 to 32
Pulsar Delays	0µs to 20µs in 2.5ns steps
Output Impedance	6 Ohms
HT Pulse Shape	Square wave
HT Pulse Voltage	Phased Array = 5 to 190V in 1V Steps Conventional = 5 to 190V in 1V steps
HT Pulse Width Range	20ns to 500ns in 2.5ns steps
Rise/fall time	< 5ns
Receiver	
Number Of Receivers	16/32/64
Number Of Active Receivers	1 to 32
Receiver Delays	0µs to 20µs in 1ns steps
Gain Range	P/E=0 to 90dB in 0.1dB steps, P/A=0 to 72dB in 0.1dB steps
Input Noise Level	2.5nV/(Hz) ½ across full system bandwidth
Input Impedance	50 Ohms
Dynamic Depth Focusing	
Operation	Dynamically optimises receive focus delays
Range Of Operation	User specified depth/range in mm or µs
Performance	100MHz real-time
Receiver DAC Curves	
Number Of Curves	1 to 8
Rate Of Gain Change	Up to 40dB/µs
A-Scan Digitizing	
A-Scan Points Per Channel	8000 samples per channel
Number Of Gates Per Channel	3 overlapping hardware Gates
Gate Start/Width	User definable in 40ns steps
Gate Reference Points	Transmit Pulse or Material Interface Echo
Storage Modes Per Gate	A-Scans, Peak Depth and Amplitude, both

Software

General Features

- Simultaneous Phased Array, ToFD & Pulse Echo data collection
- Operator definable weld geometry overlays
- Real-time A, B, C and D-Scan images, with user defined display modes
- Internal report generation including interactive print-preview & user-definable report fields
- Full cursor analysis indicating peak depth, amplitude and x,y position
- Export Bitmap images to any Windows application
- 8 or 14 bit Data collection (Phased array/Pulse Echo/ToFD)
- Import ESBeamTool® setups

Phased Array

- User configurable control of beam angle, focal distance and spot size
- Fixed-angle electronic or sectorial scans
- Dynamic Depth Focusing (DDF) provides a user-definable focal range
- 2000 Focal laws
- Supports linear probe/wedge geometry
- Normalisation of amplitude across sectorial scan angles or fixed angle focal laws
- Beam Apodization
- Skip Correction provides correct depth/range relationship for multiple legs

Signal Averaging

Number Of Channels All (128 software channels)
Averaging Rates Real-time averaging 2 - 256, user definable

Peak Processing

Peak Storage Modes All Peaks, First Peak, Largest Peak/s,
Loss of Signal, Between

Threshold Setup 5 to 100% in 1% steps per hardware Gate
Number Of Peaks Per Gate 16 max

Scanner Interface Ports

Input Type Encoder, Potentiometer, Video Camera
Number Of Axis 2 axis, TTL compatible
Encoder Interface TTL compatible, 5V @ 1A, 12V @ 0.4A
Potentiometer Interface 0 to 2.5V, sampled at 100Hz
Video Input 1Vpp Composite

PC (Internal)

Operating System Windows® 7
3rd Party Software AVG Antivirus®
ESBeamTool® (Eclipse Scientific)
Processor Intel Atom N270
Memory 2GB
Display Colour TFT (Industrial type) 8.4"
TFT Display Resolution 800 x 600 - Sunlight Readable Screen
Storage 128GB SSD
Ports 2 x USB, 1 x 10/100 Ethernet, 1 x Video

Size, Weight and Environmental

Unit Dimensions 270 x 300 x 110mm
Weight 5Kg
Temperature -10°C to 40°C operating / -25°C to 85°C storage (without batteries)

Battery Capability

Operating Time 4 Hours (approx)
DC Input 19V
AC Input 90 to 260VAC @ 40Hz to 60Hz

Pulse Echo

- Independent control of transmit and receive parameters
- C-scan with end views for corrosion mapping
- Trigger reference modes including Interface Echo or Tx Pulse
- Multiple peak data storage modes, including full/selective A-Scan storage

ToFD

- Perform multi-channel TOFD and Pulse Echo inspections simultaneously
- Full suite of image analysis tools for defect/crack sizing
- Real-time multi-channel averaging significantly improves signal quality
- Linearization, Straightening, Synthetic-Aperture-Focusing-Technique (SAFT)
- File utilities include file join, split, reverse, save partial, output data to text file etc.

Weld Zone Discrimination

- Combined TOFD, Time/Amplitude view, Map view, Couplant Check & Go/No-Go in a single pass
- Inspection data displayed as strips indicating weld zones
- Integrated TOFD analysis
- Automated report generator

E&OE - All specifications are subject to change. It is advisable to check all information provided.